









info@cfpflex.com email: www.cfpflex.com site:

DATA SHEET

100% Made in Fr	rance	DATA SHEET Date: 18/05/2021	
PRODUCT	libertuLaser™ Clear Streem s print	Laser printable TRANSPARENT A4 / A3 film for white or clear textile	
CODE	L402 S	(box of 100 sheets)	
DESCRIPTION	Heat-adhesive film on NON adhesive polyester carrier.		
THICKNESS +/-5%	Printable film: 60 microns Polyester carrier: 100 microns.		
USER'S GUIDE	 Text, photo or image must be printed mirrorwise. Use the Bypass feeding (manual feeding) of the printer, on Glossy 100/120g setting. If wanted, cut out the contours using a plotter with an optical eye function. Set up the blade to cut only the print film, and not the polyester carrier, then weed. Put the printed and weeded face directly on the textile, protect the sheet with baking paper. After a first heatpressing at 160°C / 30 seconds, peel the carrier after cooling, and press a second time at 160°C / 30 seconds, while protecting the print with baking paper. 		
	-		
WASHING TEMPERATURE	Pressure: 5 bars (70 PSI) on automatic press, maximum pressure on manual press. 60°C		
TEXTILES	Cotton - Polyester - Polycotton - Nylon (to be tested before use).		
ADVANTAGES	1. Very quick and cost saving to print with a standard CMYK laser printer 2. A professional soft touch, simple to transfer with one format only to use 3. This stretch version is especially elastic and provides great wear confort 4. A high quality full colors print with no rasterisation/RIP sofware 5. Great scalability: unit or high volume personalisation 6. Easy to cut out the contours thanks to a plotter with an optical eye function & get small details 7. Transparent carrier allows to place the image accurately on textile. 8. Universal thermoadhesive with excellent proven bonding on most textiles 9. Withstand many washing cycles up to 60°C. 10. Elastic and strong film, doesn't wrinkle after washing. 11. Ecofriendly, water based, solvent and PVC free polyurethane. 12. Low carbon profile manufacturing: all operations made under one roof 13. 100% made in France, out of european raw materials. 14. Last generation machines and exclusive manufacturing process, ensuring competitive prices 1. Wait 24 hours before washing.		
FURTHER RECOMMENDATION SAFETY	2. Do not us 3. Iron from 4. Store our	e bleach or other aggressive chemical agents.	
SAFEIT	<u> </u>	Standard 100 Class 1.	
RESUBLIMATION		on sublimated printed polyester.	
IRON ON (A4 SHE	ETS) After mirror or text direct carrier with carrier whe	cutting with scissors or by plotter, and weeding of contours, place the image city on garment, set the iron on maximum heat. Don't use any steam. Protect a baking paper. Press strongly, from the center towards the edges. Peel off n cold.	
This document is likely to be modified without notice. Please take contact with our commercial department.			