



Product video presentation



Join us on Instagram



email : info@cfpflex.com

site : www.cfpflex.com



100% Made in France

DATA SHEET

Date: 18/05/2021

PRODUCT	UNIFLEX  Sparkles <i>Special effects</i>	Plotter film with a sparkling effect for heat transfer on textiles	
CODES	111SP, 125SP, 101SP, 195SP, 116SP, 121SP, 124SP	COLOURS	fuchsia, gold, black, red, blue, green, silver
DESCRIPTION	Water based polyurethane coating, with sparkling effect, laminated between a non-adhesive polyester carrier and a heat adhesive layer.		
THICKNESS (+/-5%)	Heatadhesive polyurethane: 60 microns.		Non-adhesive Carrier film: 100 microns.
TEXTILES	Cotton - Polyester - Polycotton		
ADVANTAGES	<ol style="list-style-type: none"> 1. Quick weeding 2. Quick pressing time at low temperature: 140°C/10 seconds on cotton, polyester, polycotton 3. Universal thermoadhesive with excellent bonding on most textiles. 4. Washing resistance: short cycle at 30°C 5. Elastic and strong polyurethane, doesn't wrinkle after washings. 6. Pleasant non-adhesive carrier, easy to stack and handle. 7. Ecofriendly, water based, solvent and PVC free polyurethane. 8. Low carbon profile manufacturing: all operations made under one roof. 9. Hundred per cent made in France, out of european raw materials. 10. Last generation machines and exclusive manufacturing process, ensuring competitive prices. 		
PRESSURE	Medium (depending upon the characteristics of the press)		
PEELING	COLDPEEL		
HEATPRESSING: WITHOUT OVERLAPPING	140°C/10 seconds Washing temperature: short cycle at 30°C		
FURTHER RECOMMANDATIONS	<ol style="list-style-type: none"> 1. Not suitable for very small letters 2. Always protect Flex material from direct contact with heating plate with a release baking paper, in order to avoid any possible lifting at press opening. 3. Wait 24 hours before washing. 4. Do not use bleach or other aggressive chemical agents. 5. Iron from inside. 6. Store our products in a tempered and dry room, protected from direct sun rays. 		
SAFETY	Inert components, REACH compliant, without PVC, plastifiers, VOC, according to Oekotex Standard 100 Class 1.		
RESUBLIMATION	UNIFLEX SPARKLES can be applied on sublimated polyester. It blocks colors migration from the textile		
IRON ON	After mirror cutting with scissors or by plotter, and weeding of contours, place the image or text directly on garment, set the iron on medium heat. Don't use any vapour. Peel off carrier when cool.		

This document is likely to be modified without notice. Please take contact with our commercial department.