



email : [info@cfpflex.com](mailto:info@cfpflex.com)  
 site : [www.cfpflex.com](http://www.cfpflex.com)

## DATA SHEET

Date 27/3/2021

PRODUCT	<b>UNIPRINT A</b> Clear Matt		Print and plot film for heat transfer on white and light textiles	
CODE	305 A	COLOUR	Clear transparent	
DESCRIPTION	Printable, clear, water based, solvent and PVC free, polyurethane film, laminated on a self-adhesive carrier. For solvent, ecosolvent (including Truevis2) inks			
THICKNESS (+/-5%)	Thermo-adhesive film: 45 microns.		Self-adhesive carrier: 120 microns.	
TEXTILES	Cotton - Polyester - Polycotton ( white or light colour ) .			
ADVANTAGES	<ol style="list-style-type: none"> <li>1. Easy and accurate weeding, even of small letters.</li> <li>2. Pressing : 160°C / 15 seconds on cotton, polyester, polycotton, etc...</li> <li>3. Direct heatpressing, without application tape.</li> <li>4. Elastic and strong film, doesn't wrinkle after washings.</li> <li>6. Ecofriendly, water based, solvent and PVC free coating &amp; Vegan.</li> <li>7. Low carbon footprint: all operations made under one roof.</li> <li>8. Hundred per cent made in France, out of european raw materials.</li> <li>9. Last generation machines and exclusive manufacturing process</li> </ol>			
PRESSURE	Medium			
PEELING	WARMPEEL			
HEATPRESSING WITHOUT OVERLAPPING	All textiles	<ol style="list-style-type: none"> <li>1. In case of new textile, make preliminary trials.</li> <li>2. Print and plot <u>mirror</u> image with solvent or ecosolvent ink, and weed.</li> <li>3. Apply directly onto garment, without using application tape.</li> </ol>		
		Pressing:	160 °C / 15 seconds	
		Washing temperature:	60°C	
FURTHER RECOMMANDATIONS	<ol style="list-style-type: none"> <li>1. Always protect Print material from direct contact with heating plate with a release baking paper.</li> <li>2. Wait 24 hours before washing.</li> <li>3. Do not use bleach or other aggressive chemical agents.</li> <li>4. Iron from inside.</li> <li>5. Store our products in a tempered and dry room, protected from direct sun rays.</li> </ol>			
SAFETY	Inert components, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according to Oekotex Standard 100 Class 1.			
IRON ON	<p>After printing, cutting ( mirrorwise ) and weeding, protect the film with a baking paper, set the iron on maximum heat. Don't use any steam.</p> <p>Press strongly, from the center towards the edges. Peel the baking paper when cool.</p>			

This document is likely to be modified without notice. Please take contact with our commercial department.