



100% Made in France

Join us on



Join us on



email : info@cfpflex.com

site : www.cfpflex.com



DATA SHEET

Date : 25/08/2022

PRODUCT	UNIPRINT  Clear Stretch		Print and plot film for heat transfer on white and light textiles	
CODE	306	COLOUR	Clear transparent	
DESCRIPTION	Printable, clear, thin, stretch, water based, solvent-free and PVC-free, polyurethane film, laminated on a non-adhesive carrier. For solvent, ecosolvent (including Truevis2) inks			
THICKNESS (+/-5%)	Thermo-adhesive film: 60 microns.		Non-adhesive carrier: 100 microns.	
TEXTILES	Cotton - Polyester - Polycotton (white or light colour) .			
ADVANTAGES	<ol style="list-style-type: none"> 1. Quick weeding 2. Pressing : 160°C / 20 seconds on cotton, polyester, polycotton, etc... 3. Direct heatpressing, without application tape. 4. Elastic and strong film, doesn't wrinkle after washings. 6. Ecofriendly, water based, solvent and PVC free coating & Vegan. 7. Low carbon footprint: all operations made under one roof. 8. Hundred per cent made in France, out of european raw materials. 9. Last generation machines and exclusive manufacturing process 			
PRESSURE	Medium			
PEELING	WARMPEEL			
HEATPRESSING WITHOUT OVERLAPPING	All textiles	<ol style="list-style-type: none"> 1. In case of new textile, make preliminary trials. 2. Print and plot <u>mirror</u> image with solvent or ecosolvent ink, and weed. 3. Apply directly onto garment, without using application tape. 		
		Pressing: 160 °C / 20 seconds Washing temperature: 60°C		
FURTHER RECOMMANDATIONS	<ol style="list-style-type: none"> 1. Always protect Print material from direct contact with heating plate with a release baking paper. After peeling, you can repress again 10 sec 2. Wait 24 hours before washing. 3. Do not use bleach or other aggressive chemical agents. 4. Iron from inside. 5. Store our products in a tempered and dry room, protected from direct sun rays. 			
SAFETY	Inert components, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according to Oekotex Standard 100 Class 1.			
IRON ON	After printing, cutting (mirrorwise) and weeding, protect the film with a baking paper, set the iron on maximum heat. Don't use any steam. Press strongly, from the center towards the edges. Peel the baking paper when cool.			
This document is likely to be modified without notice. Please take contact with our commercial department.				