



100% Made in France

Product video presentation



Join us on Instagram



email : info@cfpflex.com

site : www.cfpflex.com

DATA SHEET

Date: 28/06/2023

PRODUCT	PREM'DTF™ ECO	ECO-FRIENDLY DTF solution on PET film
CODE	DTF1003	In rolls or in pack of 100 sheets (A3 / 40 cm x 50 cm)
DESCRIPTION	Eco-friendly DTF solution on PET film produced in France, designed for printing/transferring graphics using the digital DTF technology with a Matt & SOFT TOUCH finish	
Total THICKNESS	50 microns	
TEXTILES	Applicable on any textiles	
ADVANTAGES	<ol style="list-style-type: none"> 1. Matt, Soft touch and stretch finish thanks to the ECO-FRIENDLY coating 2. Warm peel 3. Special coating on the film enhance washability resistance 4. Anti-static film 5. High temperature resistant that prevents ink bleeding during the process; heat-stabilised 6. Vibrant colours and good coverage of white color 7. Non-absorbent film with no powder pollution. It keeps the ink wet, making it easier for the adhesive powder 8. Transparent film allowing the design to be seen on both sides of the film, making it easy to heat transfer 9. Stability in quality 10. Print uniformity 11. No powder pollution 12. The printable side is the coated side and is slip-resistant to facilitate the DTF printing operation 13. This high-quality printable film is suitable for any desktop or large format DTF printer 14. Gain in productivity by using DTF1003 in 200 lm: less change and less waste 15. Designed and produced in France 	
AVAILABLE DIMENSIONS	A3 or 40 cm x 50 cm sheets formats on demand	Rolls : 30/40/45/50/60/80/120 cm x 100/200 lm (<i>customised width are available on request</i>)
USER'S GUIDE	<ol style="list-style-type: none"> 1-Print the visual in mirror on the matt side of the film (coated side) with waterbased inks specific to DTF - Please refer to the inks and printers' operating instructions 2-Apply the adhesive powder manually or by using an automatic powder shaker- Please refer to the adhesive powder's operating instructions 3-Heat Transfer the visual to the textile - Please refer to the inks' and adhesive powder's operating instructions before making the transfer (application from 110°C up to 160°C (depending on the adhesive powder) - 20 seconds) 4-Remove the film WARM PEEL 	
SAFETY	Inert components, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according to Oekotex Standard 100 Class 1.	
STORAGE	Store our products in a tempered and dry room, protected from direct sun rays and humidity. After each usage, put the roll back into its protective packaging to avoid humidity	
RESUBLIMATION	On sublimated polyester, it is recommended to use our specific anti-resublimation DTF film PREM'DTF BLOCKSUB beforehand to protect the transparent film (it is a two-step process), or use our other products, such as UNIFLEX BLOCKSUB and UNIPRINT SOFT BLOCKSUB	
This document is likely to be modified without notice. Please take contact with our commercial department.		