



100% Made in France

Product video presentation



Join us on Instagram



email : info@cfpflex.com

site : www.cfpflex.com

DATA SHEET

Date: 03/08/2023

PRODUCT	PREM'DTF™ DOUBLE MATT	ECO-FRIENDLY DTF solution on PET film DOUBLE MATT
CODE	DTF2002	In rolls or in pack of 100 sheets (A3 or 40 cm x 50 cm)
DESCRIPTION	Eco-friendly DTF solution on PET film produced in France, designed for printing/transferring graphics using the digital DTF technology with a MATT and SOFT TOUCH finish - DOUBLE MATT	
THICKNESS	75 microns	
TEXTILES	Applicable on any textiles	
ADVANTAGES	<ol style="list-style-type: none"> 1. Matt, soft touch and elastic finish thanks to the special solvent-free waterbased coating 2. Double matt polyester carrier to enable a better winding and unwinding, and stacking of pieces 3. Warm peel 4. Vibrant colours (including neon) and good coverage of white colour 5. Special coating on the film enhance washability resistance 6. Anti-static film 7. High temperature resistant that prevents ink migration during the process; heat-stabilised 8. Stability in quality 9. Non-absorbent film. It keeps the ink wet, making it easier for the adhesive powder to stick to the design and avoiding ink bleeding 10. Transparent film allowing the design to be seen on both sides of the film, making it easy to heat transfer 11. Print uniformity 12. No powder pollution 13. The printable side is the coated side and is slip-resistant to facilitate the DTF printing operation 14. This high-quality printable film is suitable for any desktop or large format DTF printer 15. Designed and produced in France 	
AVAILABLE DIMENSIONS	A3 or 40 cm x 50 cm sheets formats	Rolls: 30/40/45/50/60/80/120 cm x 100 lm (<i>customised widths are available on request</i>)
USER'S GUIDE	<ol style="list-style-type: none"> 1-Print the visual in mirror on the matt side of the film (coated side) with waterbased inks specific to DTF - Please refer to the inks and printers' operating instructions 2-Apply the adhesive powder manually or by using an automatic powder shaker- Please refer to the adhesive powder's operating instructions 3-Heat Transfer the visual to the textile - (application from 110°C up to 160°C (depending on the adhesive powder) - 20 seconds). Please refer to the inks' and adhesive powder's operating instructions before making the transfer 4-Remove the film WARM PEEL 	
SAFETY	Inert components, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according to Oekotex Standard 100 Class 1.	
STORAGE	Store our products in a tempered and dry room, protected from direct sun rays and humidity. After each usage, put the roll back into its protective packaging to avoid humidity	
RESUBLIMATION	On sublimated polyester, it is recommended to use our specific anti-resublimation DTF film PREM'DTF BLOCKSUB beforehand (it is a two-step process), or with other products, such as UNIFLEX BLOCKSUB and UNIPRINT SOFT BLOCKSUB	

This document is likely to be modified without notice. Please take contact with our commercial department.