100% Made in Fra	Product video presentation	Join us on Instagram	CEKO TEX STANDARD 100 D22-2292 Hohenstein HTTI	email : <u>info@cfpflex.com</u> site : <u>www.cfpflex.com</u> Date: 03/08/2023	
PRODUCT	PREM'DTF™ ## Metallic effects	DTF METALLIC PET film Direct printing DTF & DTG technology for heat <i>transfer on textiles</i>			
CODES &COLOURS	DTF1124SC-DTF1125SC-DTF1141SC- DTF1142SC-DTF1143SC-DTF1144SC- DTF1100SC-DTF1124SPSC-DTF1125SPSC- DTF1101SPSC-DTF1109SPSC-DTF1111SPSC DTF1116SPSC-DTF1121SPSC-DTF1124HSC	Mirror effect (Silver, Gold, Orange Copper, Copper, Fuchsia, Light Blue), Glitter effect (Silver, Gold, Black, Red, Fuchsia, Blue, Green), Rainbow Diamond & Holographic Silver			
DESCRIPTION	MIRROR, RAINBOW DIAMOND, HOLOGRAPHIC, or GLITTER EFFECT with SPECIAL COATING on PET Film on non-adhesive polyester carrier produced in France, designed for printing/transferring graphics using the digital DTF & DTG printing technology				
THICKNESS	iner: 130 microns Special METALLIC/GLITTER: 20 microns				
TEXTILES	Applicable on any textile 1. Special Metallic effects finish : MIRROR, GLITTER, DIAMOND RAINBOW, and HOLOGRAPHIC effects				
ADVANTAGES	 Solvent-free waterbased coating Anti resublimation properties for sensitive polyester textiles Anti-static film Stability in quality Print uniformity No powder pollution Non-absorbent film. It keeps the ink wet, making it easier for the adhesive powder to stick to the design and voiding ink bleeding This high-quality printable film is suitable for any desktop or large format DTF or DTG printer Designed and produced in France 				
AVAILABLE DIMENSIONS	A4 and A3 sheets for	nats	Rolls : 30cms x 25lı	m and 60cms x 251m <i>(customised widths are available on request)</i>	
USER'S GUIDE	 1-Print the visual in mirror on the EXTERNAL Coated side of the roll with a DTF inks, with White ink -Please refer to the inks and printers' operating instructions - Ink white % reduction might be necessary and depends on the machine and inks. Your machine needs to provide you this possibility to adjut the % of white ink (reco 50% of white ink - to fine tune) 2-Apply the adhesive powder manually or by using an automatic powder shaker - Please refer to the adhesive powder's operating instructions 3- Make sure that adhesive powder remains only on the visual to make only your visual in Metallic 4-Heat Transfer the visual to the textile at 160°C - 20/30 seconds - Please refer to the inks' and adhesive powder's operating instructions before making the transfer 5-Remove COLD PEEL (30 minutes ideally) - if needed, you can use then a low tack application tape or lint roller to apply and remove excess material (no need to heat transfer) 6-Washing conditions: cold wash (30°C) - short cycle 				
SAFETY Inert components to Oekotex Standa		, REACH compliant, without PVC, plastifiers, heavy metals, VOC, according ard 100 Class 1.			
-		s in a tempered and dry room, protected from direct sun rays and humidity. put the roll back into its protective packaging to avoid humidity			
This document is likely to be modified without notice. Please take contact with our commercial department.					